



Filter Standard Conversion

Camfil Farr Product	MERV Per ASHRAE Standard 52.2-2007	EN779 (average @ 0.4µm)	EN1822 (MPPS)	Old ASHRAE 52. Dust Spot Efficiency (discontinued standard)	Arrestance Per ASHRAE Standard 52.2-2007
Type 44 504 panel	1	G1		<20	<65
	2	G2		<20	≥65
	3			<20	≥70
	4			<20	≥75
	5			20	80
Aeropleat® III and IV	6	G3		20-25	85
30/30®	8	G4		30-35	92
Riga-Flo® XL Hi-Flo® 45% HP® 2A	9	F5		40-45	95
Aeropac® MV11 AP-Eleven Durafil® MV11 Hi-Flo® MV11 HP® MV11 Opti-Pac MV11 Riga-Flo® MV11 Riga-Flo® MV11 Riga- Flo MV11 Riga-V MV 11	11	F6		60-65	97
Aeropac® MV13 Durafil® MV13 Hi-Flo® MV13 HP® MV13 Opti-Pac MV13 Riga-Flo® MV13 Riga-Flo® MV13 Riga- Flo MV13 Riga-V MV13	13	F7		80-85	98
Aeropac® MV14 Durafil® MV14 Hi-Flo® MV14 HP® MV14 Opti-Pac MV14 Riga-Flo® MV14 Riga-Flo® MV14 Riga- Flo MV14 Riga-V MV14	14	F8		90-95	99
Micretain® Ultra-Pac 95 DOP Filtra 2000 95 DOP	16	H10	>85	99	100
		H11	>95		
		H12	99.5		
		H13	>99.95		
		H14	>99.995		
		H15	>99.9995		
		H16	>99.99995		
		H17	> 99.999995		