

Media Holding Frame (MHF)



Advantages

- Suitable for high humidity conditions
- Replaceable filter media
- Progressively built-up thermal bonded polyester fibre

Application: Prevention of dust and dirt build up on heating/cooling coils within ventilation systems

Type: Prefilter

Frame: Mill-finished aluminium profile

Media: Polyester fibre

Temperature max: 80°C - 100°C maximum in continuous service

Holding Frame: Front and side access housings and frames are available, Type 8 and FC Housings

Fire Rating: DIN 53438 class F1



Article Number	Type	ASHRAE 52.2:2017	EN779:2012	ISO16890	Dimensions WxHxD (mm)	Air Flow/Pressure drop (m³/hr/Pa)	Media area (m²)	Weight (kg)
5402501	MHF 24x24x2-G3	MERV 6	G3	Coarse 50%	594 x 594 x 46	3400/100	0.57	1.17
5402502	MHF 12x24x2-G3	MERV 6	G3	Coarse 50%	289 x 594 x 46	1700/150	0.3	1.52
5402001	MHF 24x24x2-G4	MERV 7	G4	Coarse 60%	594 x 594 x 46	3400/110	0.57	1.69
5402002	MHF 12x24x2-G4	MERV 7	G4	Coarse 60%	289 x 594 x 46	1700/160	0.3	1.18

NGUYỄN VIỆT HOÀNG
 Sales Department.
 27 MEE Corp
 Cell: + 84 937644666
 Fax: + 84 862568463
 Email: hoang@27mec.com.vn
 Address: 340 Truong Chinh street,
 District 12, HCM city, Vietnam
 Website: www.27mec.com.vn